SAFETY DATA SHEET

NOTICE: Judgment may be based on indirect test and technical literature. The OSHA Hazard Communication Standard only requires SDS's and special labeling for materials defined as "HAZARDOUS"; see 29 CFR 1910.1200 (c). This document may be about a product which is NOT hazardous but is provided as information for our customers. See references for information.

SECTION 1. IDENTIFICATION

Product Identifier: Stick-M-Up II RTU
Product Use: Ready to use Carpet Adhesive Remover

Manufactured for: Twin-Chem, Inc.

6175 Hickory Flat Highway Canton, GA 30115 Product Identification # (PIF): 03018 Emergency Telephone #: 1-800-255-3924 General Information #: 770-924-5333 Date Prepared: November 10, 2015

SECTION 2.

HAZARD(S) IDENTIFICATION

GHS Hazard Codification:



Signal Word: WARNING

Hazard Class	Category	<u>Code</u>	Hazard Statement
Eye Irritation	2A	H319	Causes serious eye irritation
Skin Irritation	2	H315	Causes skin irritation
STOT, Single Exposure; Narcotic effects	3	H336	May cause drowsiness or dizziness

Precautionary	Code	<u>Statement</u>
Prevention	P261	Avoid breathing fumes/mists/ vapors/sprays.
	P264	Wash thoroughly after handling.
	P271	Use only outdoors or in a well-ventilated area.
	P280	Wear protective gloves/protective clothing/eye protection/face protection.
Response	P302+P352	IF ON SKIN: Wash with soap and water.
	P321	Specific treatments: See Section 4 First Aid Measures.
	P332+P313	If skin irritation occurs: Get medical advice/attention.
	P362	Take off contaminated clothing and wash before reuse.
	P304+P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
	P312	Call a POISON CENTER or doctor/physician if you feel unwell.
	P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if easy to do so. Continue
		rinsing.
	P337+P313	If eye irritation persists: Get medical advice/attention.
Storage	P403+P233	Store in a well ventilated place. Keep container tightly closed.
	P405	Store locked up.
Disposal	P501	Dispose of contents/container in compliance with all Federal, State/Provincial and local laws and regulations.

<u>Description of any hazards not otherwise classified</u>: Repeated skin exposure can cause drying and flaking of the skin (dermatitis). Inhalation of vapors/mists/sprays may cause irritation to the respiratory system, and central nervous system depression. Symptoms may include headache, dizziness, nausea, euphoria, drowsiness and fatigue. Ingestion may cause headache, dizziness, gastrointestinal distress, and rapid damage to red blood cells and subsequent anemia. Extreme overexposure may cause liver and kidney damage.

SECTION 3.

COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient	Common Names	CAS#	Concentration Range %
2-butoxyethanol	Ethylene glycol monobutyl ether	111-76-2	2 – 6
Disodium trioxosilicate	Silicic Acid, disodium salt	6834-92-0	1 – 3

SECTION 4.

FIRST AID MEASURES

<u>Eyes</u>: Flush well with water for at least 15 minutes, holding eyelids open. Remove any contact lenses and continue rinsing. If irritation persists, seek medical attention.

<u>Skin</u>: Wash well with soap and water. Remove contaminated clothing and launder before reuse. If irritation persists, seek medical attention.

Inhalation: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. If breathing is difficult, have a trained person administer oxygen. If respiration stops, have a trained person administer artificial respiration by way of pocket mask equipped with one-way valve or other proper respiratory device – Do NOT use mouth-to-mouth method if victim inhaled material. Call a physician.

<u>Ingestion</u>: DO NOT INDUCE VOMITING. Call a physician immediately. If victim is completely conscious and aware, have him rinse out mouth, then drink 8 oz. water to dilute. Never give anything by mouth to an unconscious person.

SECTION 5

FIRE-FIGHTING MEASURES

Flammability: Class IIIB Combustible liquid Flash Point: Flash Point: Above 200°F (93°C) Extinguishing Media: Foam, dry chemical, carbon dioxide fire extinguishers, water spray. Do not spray water directly on fire. Use water spray to cool containers.

Specific hazards arising from chemical: None known.

Hazardous combustion products: Carbon monoxide and carbon dioxide.

Firefighting protective equipment: Wear a self-contained breathing apparatus with a full face piece operated in the positive pressure demand mode with appropriate turn-out gear and chemical resistant personal protective equipment.

Sensitivity to static discharge: This product is combustible a Class IIIB Combustible liquid.

ACCIDENTAL RELEASE MEASURES SECTION 6.

Personal Precautions: Use personal protective equipment (Section 8). Eliminate all ignition sources. Ventilate area. Avoid breathing fumes/mists/ vapors/sprays. Do not eat, drink or smoke while handling. Wash thoroughly after handling. For Small Spills: Spilled material may be slippery. Avoid dispersal of material and runoff into soil, waterways, drains and sewers. Vapor-suppressing foam may be used to reduce vapors. Neutralize spill with mild acid, such as citric acid. Absorb spill with vermiculite or other inert material, then place in a container for chemical waste with non-sparking tools. Wash walking surfaces with water to reduce slipping hazard. Dispose of contaminated absorbent material in accordance with local, state and federal regulations.

For Large Spills: Large spills cannot occur due to packaging.

SECTION 7

HANDLING AND STORAGE

Handling: Wear personal protection equipment (Section 8). Use only outdoors or in a well-ventilated area. Avoid breathing fumes/mists/ vapors/sprays. Do not handle around sources of ignition. Never use welding or cutting torch on or near drum (even empty) because product can ignite explosively. Do not premix with other chemicals. Empty containers may contain residue and can be dangerous. Do not eat, drink or smoke in work areas. Wash thoroughly after handling.

Storage: Keep away from heat, flame, or sunlight. Keep from freezing. Keep container tightly closed when not in use. Store locked up. Store in a well-ventilated place. Protect from physical damage. Store away from oxidizers, acids, alkalis, chlorates, chlorine, organic amines, aluminum, zinc, tin, copper and their alloys.

SECTION 8.

EXPOSURE CONTROLS / PERSONAL PROTECTION

<u>Ingredient</u>	CAS#	OSHA/PEL	ACGIH/TLV	STEL_
2-Butoxyethanol	111-76-2	50ppm	20ppm	Not established
Disodium trioxosilicate	6834-92-0	Not established	Not established	Not established

Engineering Controls: Provide adequate ventilation. Observe occupational exposure limits and keep the risk of exposure to a minimum. Personal protective equipment:

Eye: Safety glasses with side shields or splash proof goggles.

Skin: Chemical resistant gloves. Normal materials handling clothing.

Respirator: Use NIOSH approved protection if PEL is exceeded or if vapors are causing irritation.

Other: Use in a well ventilated area. Do not eat, drink or smoke while handling. Wash thoroughly after handling.

SECTION 9.

PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Colorless, clear liquid	Upper/Lower flammability limits	Not determined
Odor	Mint	Vapor pressure	>0.1mmHg @ 20°C
Odor threshold	Not determined	Vapor density (Air = 1)	Not determined
pH	11.5 – 12.5	Specific gravity (water = 1.0)	1.015 g/ml
Melting point	Not determined	Solubility	Complete in water
Freezing point	Not determined	Partition coefficient (n-octanol/water)	Not determined
Boiling point	Not determined	Auto-ignition temperature	Not determined
Flash point	Above 200°F (93°C)	Decomposition temperature	Not determined
Evaporation rate (n-butyl acetate=1)	<1	Viscosity	Not determined
Flammability	Class IIIB combustible	%Volatile/Volume	97

SECTION 10.

STABILITY AND REACTIVITY

Reactivity: Contact with acids will cause gelling and evolution of heat.

Chemical stability: Stable under normal, ambient temperature and conditions.

Possibility of hazardous reactions: Hazardous polymerization will not occur.

Conditions to avoid: Heat, flame and sparks. Keep from freezing. Do not mix with other chemicals

Substances to avoid: Avoid oxidizers, acids, alkalis, chlorates, chlorine, organic amines, aluminum, zinc, tin, copper and their

Hazardous combustion products: Carbon monoxide and carbon dioxide.

SECTION 11 Acute Toxicity:

TOXICOLOGICAL INFORMATION

Oral (LD50 Rat): >5000mg/kg Dermal (LD50 Rabbit): >5000mg/kg Inhalation (LC50 Rat): >5000ppm (4hrs)

Skin corrosion irritation: Causes skin irritation. Symptoms may include redness and itching. Repeated exposure to skin can cause drying and flaking of the skin (dermatitis).

Serious eye damage/irritation: Causes serious eye irritation. Symptoms may include tearing and redness.

Respiratory or skin sensitization: Inhalation of vapors and/or mists may cause irritation to the respiratory system, and central nervous system depression. Symptoms may include headache, dizziness, nausea, euphoria, drowsiness and fatigue. Germ cell mutagenicity: No data available.

Carcinocenicity: NTP/IARC/OSHA Carcinogen: No

Reproductive toxicity: Not available

STOT-single exposure: Immediate – Skin irritant. Causes severe eye irritation. Inhalation of vapors and/or mists may cause

irritation to the respiratory system, and central nervous system depression.

STOT-repeated exposure: None known.

Aspiration hazard: Not available

<u>Ingestion:</u> May cause headache, dizziness and gastrointestinal distress. Causes rapid damage to red blood cells and subsequent anemia. Extreme overexposure may cause liver and kidney damage.

Likely routes of exposure: Eyes, skin and inhalation (if mists or sprays are generated)

Interactive effects: Not available

SECTION 12.

ECOLOGICAL INFORMATION

Toxicity:

96h LC-50 (fish): >100ppm

48h LC-50 (invertebrates): >100ppm

192h EC0 (algae): >10ppm

Persistence and degradability: No data available Bioaccumulative potential: No data available

Mobility in soil: Soil mobility not determined. This product is soluble in water and may spread in water systems. This product is partially volatile and may spread in the atmosphere.

Other adverse effects: This product can raise the pH of an aquatic environment, and thus be toxic to fish and aquatic plants. As with all chemicals, work practices should be aimed at eliminating environmental releases.

SECTION 13.

DISPOSAL CONSIDERATIONS

<u>Disposal of Wastes</u>: Do not dump into sewers, on the ground or into any waterways. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations.

<u>Contaminated Packaging</u>: Since emptied containers retain product residue, follow label warnings even after container is emptied. Do not cut, drill, grind or weld on or near the container.

RCRA: Not applicable.

SECTION 14.

TRANSPORT INFORMATION

United States D.O.T.:

Not regulated

IATA and IMDG:

Not regulated

Marine Pollutant (IMDG Code): Not listed.

Transportation in bulk (IMDG - Annex II of MARPOL 73/78 and IBC Code): Not offered in bulk for transport overseas.

SECTION 15.

REGULATORY INFORMATION

TSCA: All components of this product are on the TSCA inventory or are exempt from TSCA inventory requirements under 40 CFR 720.30.

SARA Section 302: The components of this product are either not regulated or regulated, but present in negligible concentrations. SARA TITLE III Section 311/312:

Immediate (Acute) Health	Yes	Fire Hazard	No
Delayed (Chronic) Health	No	Reactive Hazard	No

<u>SARA Title 313</u>: This material contains the following chemical components with known CAS numbers subject to reporting requirements (40 CFR 372): Ethylene Glycol Monobutyl Ether CAS# 111-76-2 % by weight = 4%.

CERCLA: This product does not have a reportable quantity.

<u>United States Right-To-Know</u>: Ethylene Glycol Monobutyl Ether CAS# 111-76-2 – California, Massachusetts, Minnesota, New Jersey & Pennsylvania.

<u>Proposition 65</u>: This material does not contain any chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

RCRA: Not applicable.

SECTION 16.

OTHER INFORMATION

Date prepared: November 10, 2015

Hazard Ratings (HMIS): Health 1, Flammability 1, Reactivity 0 (Scale 0 – 4). Personal Protection Rating to be supplied by user

based on use conditions. Product VOC: 5%

Carefully read all instructions on label before handling this product.

Keep out of reach of children. "FOR INDUSTRIAL USE ONLY"

 Abbreviation
 Full Name/Explanation

 ACGIH
 American Conference of Government Industrial Hygienists

 CAS
 Chemical Abstract Service

 CERCLA
 Comprehensive Environmental Response Compensation and Liability Act

 CNS
 Central Nervous System

 CFR
 Code of Federal Regulations

 DOT
 Department of Transportation

EC	Effective Concentration
HMIS	Hazardous Material Information System
LC	Lethal Concentration
LD	Lethal Dose
NA	Not Applicable
ND	Not Determined
NE	Not Established
NIOSH	National Institute for Occupational Safety and Health
OSHA	Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
RCRA	Resource Conservation Recovery Act
SARA	Superfund Amendments and Reauthorization Act
STEL	Short-Term Exposure Limit
STOT	Specific Target Organ Toxicity
TLV	Threshold Limit Value
TSCA	Toxic Substance Control Act
VOC	Volatile Organic Compounds

The information contained herein is based on data available to us and is believed to be correct. We make no warranty, however, expressed or implied regarding the accuracy of these data or the results obtained from the use thereof.

Regulatory Standards: DOT TITLE 49, Code of Federal Regulations 172.101: Parts 100 to 177, Revised 10/1/92.

SUPER FUND AMENDMENTS REAUTHORIZATION ACT OF 1986, TITLE III TOXIC SUBSTANCE CONTROL ACT LIST (TSCA)- INGREDIENTS LISTED. REGISTRY OF TOXIC EFFECTS OF CHEMICAL SUBSTANCES NATIONAL TOXICOLOGICAL PROGRAM (NTP) REPORT OF CARCINOGENS INTERNATIONAL AGENCY FOR RESEARCH ON CANCER (IARC) MONOGRAPHS, OCCUPATIONAL SAFETY & HEALTH REGULATIONS. CODE OF FED. REGS. FOOD & DRUG, 21 PARTS 170 to 199, Pavised 4(1/4) 173.10. Revised 4/1/91, 173.310.