



Specifications: Clean Air Citrus Low Odor Mastic Remover 5 gallon Pail and 55 Gallon Drum

Appearance:	Clear Liquid
Odor:	Citrus-like Odor
Boiling Point:	340 - 550 F
Vapor Density:	No data
pH:	No data
Flash Point:	118 F
DOT Shipping Class:	70
Shipping Weight:	5 gal. pail 37 lbs. 55 gal. drum 412 lbs.
Specific Gravity:	No data
Solubility in Water:	No data
Coverage Rate:	100 to 125 sq ft / gal
Shelf Life:	None
NMFC:	48580
DOT Shipping Name:	Not DOT Regulated on containers less than 120 gallons

Twin-Chemicals
Atlanta, Georgia

(800) 442-4958
(770) 924-6147 fax

www.twinchemicals.com



Clean Air Citrus Low Odor Mastic Remover is an economical, fast acting, CARB Compliant, low odor mastic remover. This product is a hydro-treated petroleum base with a superior surfactant system that allows for easy rinsing and final cleaning. This product is a contractor favorite because it gets the job done and is extremely cost effective.

Directions:

1. Read and understand the safety data sheet (SDS) when using this product.
2. Prepare a safe work area. Using plastic sheeting, cover walls, windows, air vents, drains, cracks, carpeting, woodwork and any other porous materials that may come in contact with the mastic remover. Set up decontamination chambers and a negative air system.
3. Remove floor tile according to local and federal regulations.
4. Apply **Clean Air Citrus** Mastic Remover to the defined areas, either manually or with a pump sprayer until areas are completely saturated. Do not let the mastic remover splash onto any porous areas (drywall, wood, etc). Agitate the product with a stiff bristled broom or brush.
5. Allow the mastic remover to penetrate and soften the adhesive for at least 20-30 minutes. Some mastic may require a longer dwell time.
6. After the mastic has dissolved, use a squeegee to collect liquefied mastic into a pile and use **Mastasorb Absorbent** bales to soak up liquid. Dispose waste according to local and federal regulations.
7. Once the adhesives have been satisfactorily removed, use a wetting agent, **Pronto Extra Wetter**, to wet out any remaining particles to make certain they don't become airborne.
8. The final step is to use a heavy-duty degreaser, **DeSolv Degreaser**, to remove residual mastic remover from the substrate and to speed up the time between mastic removal and resurfacing. The degreaser is applied straight and scrubbed into the surface as water is added, with agitation, to 'float' the solvent out of the substrate.
9. Allow the surface to dry a minimum of 48-72 hours before applying new mastic and/or new flooring.

WARRANTY NOTICE: Seller makes no warranty, expressed or implied, nor accepts any responsibility for any direct or consequential damages beyond the purchase price, because seller