REMOVER

Revision: 03/14/2017

Supersedes Revision: 03/06/2015

Page: 1 of 8

1. Product and Company Identification

Product Code: 00065R03142017

Product Name: CLEAN AIR LOW ODOR MASTIC REMOVER

Company Name: TWIN-CHEMICALS, INC Phone Number: 6175 Hickory Flat Highway (800)442-4958

Suite 110-344

Canton, GA 30115

Web site address: www.twinchemicals.com
Email address: sales@twinchemicals.com

Emergency Contact: CHEMTREC (emergency only) (800)424-9300 **Information:** Sales & Information (800)442-4958

2. Hazards Identification

Flammable Liquids, Category 4
Acute Toxicity: Skin, Category 4
Skin Corrosion/Irritation, Category 2
Aspiration Toxicity, Category 1

Acute Toxicity: Inhalation, Category 4

Serious Eye Damage/Eye Irritation, Category 2A

Acute Toxicity: Oral, Category 4
Aquatic Toxicity (Acute), Category 2
Aquatic Toxicity (Chronic), Category 2







GHS Signal Word: Danger

GHS Hazard Phrases: H227 - Combustible liquid.

H302+312+332 - Harmfull if swallowed, in contact with skin or if inhaled.

H304 - May be fatal if swallowed and enters airways. H312+332 - Harmfull in contact with skin or if inhaled.

H315 - Causes skin irritation.

H319 - Causes serious eye irritation.

H411 - Toxic to aquatic life with long lasting effects.

GHS Precaution Phrases: P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P261 - Avoid breathing mist/vapours/spray. P264 - Wash hands thoroughly after handling.

P270 - Do not eat, drink or smoke when using this product. P271 - Use only outdoors or in a well-ventilated area.

P273 - Avoid release to the environment.

P280 - Wear protective gloves/protective clothing/eye protection.

GHS Response Phrases: P301+310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P312 - Call a POISON CENTER or doctor/physician if you feel unwell.

P302+352 - IF ON SKIN: Wash with plenty of soap and water.

P304+340 - IF INHALED: Remove victim to fresh air and keep at rest in a position

comfortable for breathing.

P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison control center or physician for treatment advice. Have product container or label with you when calling

poison control center or physician.

P330 - Rinse mouth.

REMOVER

Revision: 03/14/2017 Supersedes Revision: 03/06/2015

Page: 2 of 8

P331 - Do NOT induce vomiting.

P332+313 - If skin irritation occurs, get medical advice/attention.
P337+313 - If eye irritation persists, get medical advice/attention.
P362 - Take off contaminated clothing and wash before re-use.

P363 - Wash contaminated clothing before reuse.

P391 - Collect spillage.

P370+378 - In case of fire, use water fog, dry chemical, carbon dioxide or foam to

extinguish.

GHS Storage and Disposal

P403+235 - Store in cool/well-ventilated place.

Phrases: P405 - Store locked up.

P501 - Dispose of contents/container to a waste facility according to all local regulations.

Potential Health Effects (Acute and Chronic):

Prolonged or repeated skin contact may cause defatting and dermatitis.

Chronic: May cause liver and kidney damage. Sophisticated modeling has clearly proven

that 2-butoxyethanol does not build up in the body under any kinds of normal use.

Inhalation: Harmful if inhaled. May cause narcotic effects in high concentration. May cause lung

damage. May cause central nervous system effects such as nausea and headache.

Material is irritating to mucous membranes and upper respiratory tract.

Skin Contact: Causes skin irritation. Causes symptoms similar to those of inhalation. Skin sensitization

testing with human volunteers produced negative results. A skin notation is not recommended by ACGIH, based on estimates from physiologically based

pharmacokinetic models which indicate that, even in worst-case dermal-exposure

scenarios, 2-butoxyethanol is not absorbed in amounts sufficient to cause red blood cell

hemolysis in humans. May cause skin irritation.

Eye Contact: Causes redness and pain. Causes severe eye irritation.

Ingestion: Aspiration hazard. May cause irritation of the digestive tract. Harmful if swallowed. May

cause gastrointestinal irritation with nausea, vomiting and diarrhea. Prolonged or repeated exposure may cause allergic reactions in certain sensitive individuals.

3. Composition/Information on Ingredients

CAS#	Hazardous Components (Chemical Name)	Concentration
64742-47-8	Hydrotreated light distillate (petroleum)	80.0 -90.0 %
111-76-2	Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, Glycol Ether EB}	10.0 -15.0 %
9016-45-9	Poly(oxy-1,2-ethanediyl), .alpha(nonylphenyl)omegahydr {Nonylphenol Ethoxylate}	3.0 -6.0 %

REMOVER

Revision: 03/14/2017 Supersedes Revision: 03/06/2015

Page: 3 of 8

4. First Aid Measures

Emergency and First Aid

Procedures:

In Case of Inhalation: If inhaled, remove to fresh air. If breathing is difficult, give oxygen. Get medical aid

immediately. Remove from exposure and move to fresh air immediately.

In case of contact, flush skin with plenty of water. Remove contaminated clothing and In Case of Skin Contact:

shoes. Get medical aid if irritation develops and persists. Wash clothing before reuse.

In Case of Eye Contact: In case of contact, immediately flush eyes with plenty of water for a t least 15 minutes.

Get medical aid immediately.

In Case of Ingestion: Potential for aspiration if swallowed. Get medical aid immediately. Never give anything

> by mouth to an unconscious person. If vomiting occurs naturally, have victim lean forward. Call a poison control center. If swallowed, wash out mouth with water provided

person is conscious. Call a physician.

Signs and Symptoms Of

Exposure:

Exposure can cause: Nausea, headache, and vomiting.

Note to Physician: None known.

5. Fire Fighting Measures

79.00 C Method Used: Cleveland Open Cup Flash Pt:

LEL: 0.6 UEL: 7.0 **Explosive Limits:**

> 231.00 C Autoignition Pt:

Suitable Extinguishing Media: Use water spray, dry chemical, carbon dioxide, or appropriate foam. Suitable:

As in any fire, wear a self-contained breathing apparatus in pressure-demand, Fire Fighting Instructions:

> MSHA/NIOSH (approved or equivalent), and full protective gear. During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion. Use

water spray to keep fire-exposed containers cool. Will burn if involved in a fire. Combustible liquid and vapor. Protective Equipment: Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes. Specific

Hazard(s):

Flammable Properties and

Hazards:

No data available.

Hazardous Combustion

Products:

No data available.

6. Accidental Release Measures

Protective Precautions. Protective Equipment and Emergency Procedures:

Hand: Compatible chemical-resistant gloves. Always use a NIOSH or European Standard EN 149 approved respirator when necessary. Eye protection is recommended.

Environmental Precautions:

Do not discharge directly into the environment or into the sewer system.

Steps To Be Taken In Case Material Is Released Or

Use proper personal protective equipment as indicated in Section 8.

Spilled:

Spills/Leaks: Avoid runoff into storm sewers and ditches which lead to waterways. Clean up spills immediately, observing precautions in the Protective Equipment section. Remove all sources of ignition. Provide ventilation. Do not let this chemical enter the

environment. PROCEDURE(S) OF PERSONAL PRECAUTION(S)

Wear respirator, chemical safety goggles, rubber boots, and heavy rubber gloves.

Methods for cleaning up.

Absorb on sand or vermiculite and place in closed containers for disposal. Ventilate area

and wash spill site after material pickup is complete.

Page: 4 of 8

Revision: 03/14/2017

Supersedes Revision: 03/06/2015

SAFETY DATA SHEET CLEAN AIR LOW ODOR MASTIC **REMOVER**

Handling and Storage

Precautions To Be Taken in Handling:

Wash thoroughly after handling. Use with adequate ventilation. Avoid contact with eyes, skin, and clothing. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep container tightly closed. Avoid ingestion and inhalation. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose empty containers to heat, sparks or open flames. Keep away from heat, sparks and flame. Do not ingest or inhale. User Exposure: Do not breathe vapor.

Precautions To Be Taken in Storing:

Keep away from sources of ignition. Store in a tightly closed container. Store in a cool, dry, well-ventilated area away from incompatible substances.

8. Exposure Controls/Personal Protection						
CAS#	Partial Chemical Name	OSHA TWA	ACGIH TWA	Other Limits		
64742-47-8	Hydrotreated light distillate (petroleum)	No data.	TLV: 200 mg/m3	No data.		
111-76-2	Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, Glycol Ether EB}	PEL: 50 ppm	TLV: 20 ppm	No data.		
9016-45-9	Poly(oxy-1,2-ethanediyl), .alpha(nonylphenyl)omegahydr {Nonylphenol Ethoxylate}	No data.	No data.	No data.		

Personal Protective Equipment Symbols:







Respiratory Equipment

(Specify Type):

Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi- purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. Hand: Compatible

chemical-resistant gloves.

Eye Protection: Wear appropriate protective eyeglasses or chemical safety goggles as described by

OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard

EN166. Chemical safety goggles.

Wear appropriate protective gloves to prevent skin exposure. **Protective Gloves:**

Other Protective Clothing:

Engineering Controls

(Ventilation etc.):

Wear appropriate protective clothing to prevent skin exposure.

Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Use adequate ventilation to keep airborne concentrations low. Use explosion-proof ventilation equipment. Use only under a chemical fume hood. Safety

shower and eye bath.

Work/Hygienic/Maintenance

Practices:

Wash thoroughly after handling.

REMOVER

Page: 5 of 8

Revision: 03/14/2017 Supersedes Revision: 03/06/2015

9. Physical and Chemical Properties

[X] Liquid [] Gas **Physical States:** [] Solid

Clear liquid. Appearance and Odor:

solvent odor.

NΡ pH:

Freezing Point: < -70.00 C

210.00 C - 288.00 C **Boiling Point:**

Flash Pt: 79.00 C Method Used: Cleveland Open Cup

.05 MM HG

> 5 (BuAC=1) **Evaporation Rate:** No data available. Flammability (solid, gas):

LEL: 0.6 UEL: 7.0 **Explosive Limits:**

Vapor Pressure (vs. Air or

mm Hg):

Vapor Density (vs. Air = 1): NA

Specific Gravity (Water = 1): 0.800 - 0.820 at 20.0 C

NΡ Density: Nil Solubility in Water: NA Saturated Vapor

Concentration:

Octanol/Water Partition

No data.

Coefficient:

> 94.0 % by weight. **Percent Volatile:**

> 231.00 C Autoignition Pt: **Decomposition Temperature:** No data. Water thin Viscosity:

10. Stability and Reactivity

Stability: Unstable [] Stable [X]

Conditions To Avoid -

ignition sources, Incompatible materials.

Instability:

Incompatibility - Materials To Strong acids. Strong bases, Oxidizing agents.

Avoid:

Hazardous Decomposition or Carbon monoxide, oxides of sulfur.

Byproducts:

Possibility of Hazardous

Will not occur [X] Will occur []

Reactions:

Conditions To Avoid -

No data available.

Hazardous Reactions:

REMOVER

Revision: 03/14/2017

Supersedes Revision: 03/06/2015

Page: 6 of 8

11. Toxicological Information

Toxicological Information: Epidemiology: No information found.

Teratogenicity: No information available. Reproductive Effects: Mutagenicity:

Neurotoxicity:

Carcinogenicity/Other Information:

CAS# 64742-47-8: Not listed by ACGIH, IARC, NTP, or CA Prop 65. CAS# 111-76-2: ACGIH: A3 - Confirmed animal carcinogen with unknown relevance to humans.

California: Not listed.
NTP: Not listed.
IARC: Not listed.

CAS#	Hazardous Components (Chemical Name)	NTP	IARC	ACGIH	OSHA
64742-47-8	Hydrotreated light distillate (petroleum)	n.a.	n.a.	A4	n.a.
111-76-2	Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, Glycol Ether EB}	n.a.	3	А3	n.a.
9016-45-9	Poly(oxy-1,2-ethanediyl), .alpha(nonylphenyl)omegahydr {Nonylphenol	n.a.	n.a.	n.a.	n.a.

Ethoxylate}

12. Ecological Information

General Ecological Information:

Environmental: TERRESTRIAL FATE: Based on a recommended classification scheme, an estimated Koc value of 67,, determined from an experimental log Kow and a recommended regression-derived equation, indicates that ethylene glycol mono-n-butyl ether is expected to have high mobility in soil. An estimated BCF value of 2.5 was calculated for ethylene glycol mono-n-butyl ether, using an experimental log Kow of 0.83 and a recommended regression-derived equation. According to a recommended classification scheme, this BCF value suggests that bioconcentration in aquatic organisms is low.

Physical: No information found.

Other: An estimated BCF value of 2.5,, from an experimental log Kow, suggests that ethylene glycol mono-n-butyl ether bioconcentration in aquatic organisms will be low, according to a recommended classification scheme. ELIMINATION.

13. Disposal Considerations

Waste Disposal Method:

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. US EPA guidelines for the classification determination are listed in 40 CFR Parts 261. Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification.

RCRA P-Series: None listed.

RCRA U-Series: None listed. Empty container may be recycled or disposed of as solid sanitary waste. Do not reuse container. Contact a licensed professional waste disposal service to dispose of this material. Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber.

14. Transport Information

Page: 7 of 8

Revision: 03/14/2017 Supersedes Revision: 03/06/2015

LAND TRANSPORT (US DOT):

DOT Proper Shipping Name: Environmentally hazardous substance, liquid, n.o.s

(applies to single containers of more than 119 gallons -

smaller containers are not regulated)

NOT REGULATED FOR DOMESTIC TRANSPORT.

DOT Hazard Class: UN/NA Number:

LAND TRANSPORT (Canadian TDG):

TDG Shipping Name: Environmentally hazardous substance, liquid, n.o.s

(applies to single containers of more than 119 gallons -

smaller containers are not regulated)

AIR TRANSPORT (ICAO/IATA):

ICAO/IATA Shipping Name: Non-Hazardous for Air Transport: Non-hazardous for air transport.

15. Regulatory Information

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS # 64742-47-8	Hazardous Components (Chemical Name) Hydrotreated light distillate (petroleum)	S. 302 (EHS) No	S. 304 RQ No	S. 313 (TRI) No
111-76-2	Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, Glycol Ether EB}	No	No	Yes-Cat. N230
9016-45-9	Poly(oxy-1,2-ethanediyl), .alpha(nonylphenyl)omegahydr {Nonylphenol Ethoxylate}	No	No	No
CAS#	Hazardous Components (Chemical Name)	Other US EPA or S	State Lists	
64742-47-8	Hydrotreated light distillate (petroleum)	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No		
111-76-2	Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, Glycol Ether EB}	CAA HAP,ODC: Yes - Cat.; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No		
9016-45-9	Poly(oxy-1,2-ethanediyl),	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes -		

.alpha.-(nonylphenyl)-.omega.-hydr {Nonylphenol

16. Other Information

Revision Date: 03/14/2017

Ethoxylate}

HEALTH 1
FLAMMABILITY 2
REACTIVITY | PPE I

HMIS:

Additional Information About No data available.

This Product:

Company Policy or

Hazard Rating System:

Disclaimer:

THE INFORMATION CONTAINED HEREIN is based upon available information at the time of preparation and is believed to be accurate but is not warranted to be so. Users are advised to confirm in advance of need that the information is current, applicable and suited to the circumstances of use. Vendor assumes no responsibility for injury to vendee or any other user proximately caused by the material if misused or if reasonable safety procedures are not adheared to as stipulated in the data sheet and on the product label. Furthermore, vendor assumes no responsibility for injury or damage caused by

Inventory, 8A PAIR, 12(b); CA PROP.65: No

REMOVER

Revision: 03/14/2017 Supersedes Revision: 03/06/2015

Page: 8 of 8

abnormal use of this material even if reasoinable safety measures are followed.