



TWIN CHEMICALS, INC.

Specifications: Pronto EXTRA-Wetter Concentrated Surfactant 5 gallon pails

Appearance:	Clear Blue Liquid
Odor:	Bland
Boiling Point:	~ 100.00 C
Vapor Density:	Not Determined
pH:	6.0—8.0
Flash Point:	N/A
DOT Shipping Class:	55
Shipping Weight:	5 gal. pail 45lbs. 55 gal. drum 495lbs
Specific Gravity:	1.01 at 20.0 C
Solubility:	Miscible
Percent Volatile:	> 80.0% by weight
VOC / Volume:	0.0000 G/L
HFIS Rating:	1-0-0
DOT Shipping Name:	Not hazardous

**Twin-Chemicals
Atlanta, Georgia**

**(800) 442-4958
(770) 924-6147 fax**

www.twinchemicals.com



EXTRA-Wetter is effective in reducing asbestos fiber counts during removal and demolition operations. By using EXTRA-WETTER, the volume of water needed to wet and control the spread of dust and fiber particulate is reduced. This will aid in keeping work areas less messy. EXTRA-WETTER keeps particles wetter longer with less mess and with less application time by breaking up water droplets into finer mist, covering surfaces faster. Dilute 1:200. Diluted, surface tension is reduced from 100 dynes/sq.cm to 29 dynes/sq. cm, ASTM #D 1331. **NON-FLAMMABLE.**

Directions:

1. Read and understand material safety data sheet when using this product.
2. Apply EXTRA-WETTER with any suitable low pressure spray applicator.
3. Mix one part EXTRA-WETTER with 200 parts water and spray onto all surfaces until thoroughly wetted. Use a course spray. Do not atomize.
4. Reapply when surfaces start to dry. Coverage and reapplication intervals will depend on surface characteristics, temperature and humidity.



TWIN CHEMICALS, INC.

(800) 442-4958 / (770) 924-6147 Fax
www.twin-chemicals.com
©2010 Twin Chemicals, Inc.



No part of this publication may be reproduced or transmitted without the written consent of Twin Chemicals, Inc.