



Specifications: Pronto EXTRA-Wetter Concentrated Surfactant 5 gallon pails

Appearance:	Clear
Odor:	Mild
Boiling Point:	392 F
Vapor Density:	Not Determined
pH:	6.5—7.5
Flash Point:	460 F
DOT Shipping Class:	55
Shipping Weight:	5 gal. pail 45lbs. 55 gal. drum 495lbs
Specific Gravity:	1.06
Solubility:	Soluble
Reactivity:	Stable
HFIS Rating:	1-0-1
DOT Shipping Name:	Not hazardous

Twin-Chemicals
Atlanta, Georgia

(800) 442-4958
(770) 924-6147 fax

www.twinchemicals.com



EXTRA-Wetter is effective in reducing asbestos fiber counts during removal and demolition operations. By using EXTRA-WETTER, the volume of water needed to wet our and control the spread of dust and fiber particulate is reduced. This will aid in keeping work areas less messy. EXTRA-WETTER keeps particles wetter longer with less mess and with less application time by breaking up water droplets into finer mist, covering surfaces faster. Dilute 1:200. Diluted, surface tension is reduced from 100 dynes/sq.cm to 29 dynes/sq. cm, ASTM #D 1331. **NON-FLAMMABLE.**

Directions:

1. Read and understand Safety Data Sheet (SDS) when using this product.
2. Apply EXTRA-WETTER with any suitable low pressure spray applicator.
3. Mix one part EXTRA-WETTER with 200 parts water and spray onto all surfaces until thoroughly wetted. Use a course spray. Do not atomize.
4. Reapply when surfaces start to dry. Coverage and reapplication intervals will depend on surface characteristics, temperature and humidity.