



TWIN CHEMICALS, INC.

Specifications: Pronto EXTRA-Wetter Concentrated Surfactant 5 gallon pails

| | |
|---------------------|-------------------------------------------|
| Appearance: | Clear |
| Odor: | Mild |
| Boiling Point: | 392 F |
| Vapor Density: | Not Determined |
| pH: | 6.5—7.5 |
| Flash Point: | 460 F |
| DOT Shipping Class: | 55 |
| Shipping Weight: | 5 gal. pail 45lbs. 55 gal. drum 495lbs |
| Specific Gravity: | 1.06 |
| Solubility: | Soluable |
| Reactivity: | Stable |
| HFIS Rating: | 1-0-1 |
| DOT Shipping Name: | Not hazardous |

**Twin-Chemicals
Atlanta, Georgia**

**(800) 442-4958
(770) 924-6147 fax**

www.twinchemicals.com



EXTRA-Wetter is effective in reducing asbestos fiber counts during removal and demolition operations. By using EXTRA-WETTER, the volume of water needed to wet and control the spread of dust and fiber particulate is reduced. This will aid in keeping work areas less messy. EXTRA-WETTER keeps particles wetter longer with less mess and with less application time by breaking up water droplets into finer mist, covering surfaces faster. Dilute 1:200. Diluted, surface tension is reduced from 100 dynes/sq.cm to 29 dynes/sq. cm, ASTM #D 1331. **NON-FLAMMABLE.**

Directions:

1. Read and understand Safety Data Sheet (SDS) when using this product.
2. Apply EXTRA-WETTER with any suitable low pressure spray applicator.
3. Mix one part EXTRA-WETTER with 200 parts water and spray onto all surfaces until thoroughly wetted. Use a course spray. Do not atomize.
4. Reapply when surfaces start to dry. Coverage and reapplication intervals will depend on surface characteristics, temperature and humidity.



TWIN CHEMICALS, INC.

(800) 442-4958 / (770) 924-6147 Fax
www.twinchemicals.com

©2010 Twin Chemicals, Inc.



No part of this publication may be reproduced or transmitted without the written consent of Twin Chemicals, Inc.