Revision: 02/11/2020 Supersedes Revision: 12/04/2019

	1. Product and Company Iden	tification
Product Code:	00067R02112019	
Product Name:	PROCLEAN NO ODOR MASTIC REMOVER	
Company Name:	TWIN-CHEMICALS, INC.	Phone Number:
	6175 Hickory Flat Highway	(800)442-4958
	Suit 100-244	
	Canton, GA 30115	
Web site address:	www.twinchemicals.com	
Email address:	sales@twinchemicals.com	
Emergency Contact:	CERTS (Human/Environment exposure)	(800)552-3787
Information:	Information	(800)442-4958

#### 2. Hazards Identification

Flammable Liquids, Category 4 Acute Toxicity: Skin, Category 4 Skin Corrosion/Irritation, Category 2 **Aspiration Toxicity, Category 1** Acute Toxicity: Inhalation, Category 4 Acute Toxicity: Oral, Category 4 Serious Eye Damage/Eye Irritation, Category 2A Aquatic Toxicity (Acute), Category 2 Aquatic Toxicity (Chronic), Category 2



GHS Signal Word:	Danger
GHS Hazard Phrases:	H227 - Combustible liquid.
	H302+312+332 - Harmfull if swallowed, in contact with skin or if inhaled.
	H304 - May be fatal if swallowed and enters airways.
	H312+332 - Harmfull in contact with skin or if inhaled.
	H315 - Causes skin irritation.
	H319 - Causes serious eye irritation.
	H411 - Toxic to aquatic life with long lasting effects.
GHS Precautionary Phrases:	P210 - Keep away from heat/sparks/open flames/hot surfaces No smoking.
	P261 - Avoid breathing mist/vapours/spray.
	P264 - Wash hands thoroughly after handling.
	P270 - Do not eat, drink or smoke when using this product.
	P271 - Use only outdoors or in a well-ventilated area.
	P273 - Avoid release to the environment.
	P280 - Wear protective gloves/protective clothing/eye protection.
GHS Response Phrases:	P301+310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. P312 - Call a POISON CENTER or doctor/physician if you feel unwell.
	P302+352 - IF ON SKIN: Wash with plenty of soap and water.
	P302+332 - IF ON SKIN. Wash with plenty of soap and water. P304+340 - IF INHALED: Remove victim to fresh air and keep at rest in a position
	comfortable for breathing.
	P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove
	contact lenses, if present and easy to do. Continue rinsing. Call a poison control center
	or physician for treatment advice. Have product container or label with you when calling
	poison control center or physician.
	P330 - Rinse mouth.

Revision: 02/11/2020 Supersedes Revision: 12/04/2019

GHS Storage and Disposal Phrases:	<ul> <li>P331 - Do NOT induce vomiting.</li> <li>P370+378 - In case of fire, use water mist, dry chemical, carbon dioxide or foam to extinguish. P332+313 - If skin irritation occurs, get medical advice/attention.</li> <li>P337+313 - If eye irritation persists, get medical advice/attention.</li> <li>P362 - Take off contaminated clothing and wash before re-use.</li> <li>P363 - Wash contaminated clothing before reuse.</li> <li>P391 - Collect spillage.</li> <li>P403+235 - Store in cool/well-ventilated place.</li> <li>P405 - Store locked up.</li> </ul>
Potential Health Effects	P501 - Dispose of contents/container to a waste facility according to local regulations. Prolonged or repeated skin contact may cause defatting and dermatitis.
(Acute and Chronic):	Chronic: May cause liver and kidney damage. Sophisticated modeling has clearly proven that 2-butoxyethanol does not build up in the body under any kinds of normal use.
Inhalation:	Harmful if inhaled. May cause narcotic effects in high concentration. May cause lung damage. May cause central nervous system effects such as nausea and headache. Material is irritating to mucous membranes and upper respiratory tract.
Skin Contact:	Causes skin irritation. Causes symptoms similar to those of inhalation. Skin sensitization testing with human volunteers produced negative results. A skin notation is not recommended by ACGIH, based on estimates from physiologically based pharmacokinetic models which indicate that, even in worst-case dermal-exposure scenarios, 2-butoxyethanol is not absorbed in amounts sufficient to cause red blood cell hemolysis in humans. May cause skin irritation.
Eye Contact:	Causes redness and pain. Causes severe eye irritation.
Ingestion:	Aspiration hazard. May cause irritation of the digestive tract. Harmful if swallowed. May cause gastrointestinal irritation with nausea, vomiting and diarrhea. Prolonged or repeated exposure may cause allergic reactions in certain sensitive individuals.
2	Composition/Information on Ingradiante

#### 3. Composition/Information on Ingredients

CAS #	Hazardous Components (Chemical Name)	Concentration
64742-47-8	Hydrotreated light distillate (petroleum)	80.0 -90.0 %
111-76-2	Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, Glycol Ether EB}	10.0 -15.0 %
9016-45-9	Poly(oxy-1,2-ethanediyl), .alpha(nonylphenyl)omegahydr {Nonylphenol Ethoxylate}	3.0 -6.0 %

	4. First Aid Measures
Emergency and First Aid Procedures:	
In Case of Inhalation:	If inhaled, remove to fresh air. If breathing is difficult, give oxygen. Get medical aid immediately. Remove from exposure and move to fresh air immediately.
In Case of Skin Contact:	In case of contact, flush skin with plenty of water. Remove contaminated clothing and shoes. Get medical aid if irritation develops and persists. Wash clothing before reuse.
In Case of Eye Contact:	In case of contact, immediately flush eyes with plenty of water for a t least 15 minutes. Get medical aid immediately.
In Case of Ingestion:	Potential for aspiration if swallowed. Get medical aid immediately. Never give anything by mouth to an unconscious person. If vomiting occurs naturally, have victim lean forward. Call a poison control center. If swallowed, wash out mouth with water provided person is conscious. Call a physician.
Signs and Symptoms Of Exposure:	Exposure can cause: Nausea, headache, and vomiting.
Note to Physician:	None known.
	5. Fire Fighting Measures
Flash Pt:	63.00 C Method Used: Cleveland Open Cup
Explosive Limits:	LEL: 0.7 UEL: 7.0
Autoignition Pt:	> 216.00 C
	a:Use water spray, dry chemical, carbon dioxide, or appropriate foam. Suitable:
Fire Fighting Instructions:	As in any fire, wear a self-contained breathing apparatus in pressure-demand, MSHA/NIOSH (approved or equivalent), and full protective gear. During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion. Use water spray to keep fire-exposed containers cool. Will burn if involved in a fire. Combustible liquid and vapor. Protective Equipment: Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes. Specific Hazard(s):
Flammable Properties and Hazards:	No data available.
Hazardous Combustion Products:	No data available.
	6. Accidental Release Measures
Protective Precautions, Protective Equipment and Emergency Procedures:	Hand: Compatible chemical-resistant gloves. Always use a NIOSH or European Standard EN 149 approved respirator when necessary. Eye protection is recommended.
<b>Environmental Precautions:</b>	Do not discharge directly into the environment or into the sewer system.
Steps To Be Taken In Case Material Is Released Or Spilled:	Use proper personal protective equipment as indicated in Section 8. Spills/Leaks: Avoid runoff into storm sewers and ditches which lead to waterways. Clean up spills immediately, observing precautions in the Protective Equipment section. Remove all sources of ignition. Provide ventilation. Do not let this chemical enter the environment. PROCEDURE(S) OF PERSONAL PRECAUTION(S) Wear respirator, chemical safety goggles, rubber boots, and heavy rubber gloves. Methods for cleaning up. Absorb on sand or vermiculite and place in closed containers for disposal. Ventilate area and wash spill site after material pickup is complete.

				Supersee	
		7. Ha	ndling and St	orage	
Precautions Handling:	To Be Taken in	skin, and clothing. can be dangerous. pressurize, cut, we sparks or open flar	Empty containers re Keep container tigh ld, braze, solder, dril	ith adequate ventilation. Avertian product residue, (liquid tly closed. Avoid ingestion a II, grind, or expose empty co n heat, sparks and flame. De	and/or vapor), and nd inhalation. Do not ontainers to heat,
Precautions Storing:	To Be Taken in		•	ore in a tightly closed contai ompatible substances.	ner. Store in a cool,
	8	. Exposure C	ontrols/Perso	nal Protection	
CAS #	Partial Chemical	Name	OSHA TWA	ACGIH TWA	Other Limits
64742-47-8	Hydrotreated light	t distillate (petroleum)	No data.	TLV: 200 mg/m3	No data.
111-76-2	Ethanol, 2-Butoxy n-butyl ether, Glyd	<ul> <li>{Ethylene glycol</li> <li>col Ether EB}</li> </ul>	PEL: 50 ppm	TLV: 20 ppm	No data.
9016-45-9	Poly(oxy-1,2-etha .alpha(nonylphe {Nonylphenol Eth	nyl)omegahydr	No data.	No data.	No data.
CAS #	Chemical Name	Jurisdiction	Recommended	d Exposure Limits	Notations
	thanol, 2-Butoxy- col n-butyl ether, Gly	NIOSH	TWA: 5 ppm		
Personal Pro		❤ ₩			
Respiratory (Specify Typ		Standard EN 149. use a full-face resp	Where risk assessm pirator with multi- pur s as a backup to eng	found in 29 CFR 1910.134 ent shows air-purifying resp pose combination (US) or ty gineering controls. Hand: Co	irators are appropriate vpe ABEK (EN 14387)
Eye Protecti	ion:		ace protection regula	s or chemical safety goggles tions in 29 CFR 1910.133 o	
Protective G	loves:	Wear appropriate p	protective gloves to p	prevent skin exposure.	
Other Protect	ctive Clothing:	Wear appropriate p	protective clothing to	prevent skin exposure.	
Engineering (Ventilation		a safety shower. U	se adequate ventilat	al should be equipped with a ion to keep airborne concen Use only under a chemical f	trations low. Use
Work/Hygier Practices:	nic/Maintenance	Wash thoroughly a	fter handling.		

	9. Physical and Chemical Properties
Physical States:	[]Gas [X]Liquid []Solid
Appearance and Odor:	Clear liquid.
	solvent odor.
pH:	NP
Freezing Point:	< -70.00 C
Boiling Point:	199.00 C - 211.00 C
Flash Pt:	63.00 C Method Used: Cleveland Open Cup
Evaporation Rate:	> 5 (BuAC=1)
Flammability (solid, gas):	No data available.
Explosive Limits:	LEL: 0.7 UEL: 7.0
Vapor Pressure (vs. Air or	.05 MM_HG
mm Hg):	
Vapor Density (vs. Air = 1):	NA
Specific Gravity (Water = 1):	0.800 - 0.820 at 20.0 C
Density:	NP
Solubility in Water:	Nil
Saturated Vapor	NA
Concentration: Octanol/Water Partition	No data.
Coefficient:	No data.
Percent Volatile:	> 94.0 % by weight.
Autoignition Pt:	> 216.00 C
Decomposition Temperature	
Viscosity:	Water thin
	10. Stability and Reactivity
Stability:	Unstable [ ] Stable [ X ]
Conditions To Avoid -	ignition sources, Incompatible materials.
Instability:	ignition sources, incompatible materials.
Incompatibility - Materials To	Strong acids. Strong bases, Oxidizing agents.
Avoid:	
Hazardous Decomposition o Byproducts:	r Carbon monoxide, oxides of sulfur.
Possibility of Hazardous Reactions:	Will occur [ ] Will not occur [ X ]
Conditions To Avoid - Hazardous Reactions:	No data available.

		11. Toxicological Inf	ormatio	on		
Toxicologica	I Information:	Epidemiology: No information found. Teratogenicity: No information availa Neurotoxicity:	ble. Repro	ductive Effect	s: Mutagenic	ity:
Carcinogenic Information:	ity/Other	CAS# 64742-47-8: Not listed by ACG ACGIH: A3 - Confirmed animal carcin California: Not listed. NTP: Not listed. IARC: Not listed.			•	
CAS #	Hazardous Con	nponents (Chemical Name)	NTP	IARC	ACGIH	OSHA
64742-47-8	Hydrotreated lig	ht distillate (petroleum)	n.a.	n.a.	A4	n.a.
111-76-2	Ethanol, 2-Butox Ether EB}	ky- {Ethylene glycol n-butyl ether, Glycol	n.a.	3	A3	n.a.
9016-45-9	9016-45-9 Poly(oxy-1,2-ethanediyl), n.a. n.a. n.a. n.a. n.a. n.a. .alpha(nonylphenyl)omegahydr {Nonylphenol Ethoxylate}			n.a.		
		12. Ecological Info	rmation			
Information:		an estimated Koc value of 67,, detern recommended regression-derived ec- ether is expected to have high mobili calculated for ethylene glycol mono-r and a recommended regression-deri classification scheme, this BCF value organisms is low. Physical: No information found. Other: An estimated BCF value of 2.4 ethylene glycol mono-n-butyl ether b according to a recommended classifi	uation, indi ty in soil. A n-butyl ethe ved equation suggests 5,, from an ioconcentra	icates that et n estimated f er, using an er on. According that bioconce experimental ation in aquat	hylene glycol BCF value of xperimental lo to a recommentation entration in ac log Kow, sug ic organisms	mono-n-butyl 2.5 was og Kow of 0.83 lended quatic ggests that
		13. Disposal Consid	leration	S		
Waste Dispo	sal Method:	Chemical waste generators must det as a hazardous waste. US EPA guid in 40 CFR Parts 261. Additionally, wa hazardous waste regulations to ensu RCRA P-Series: None listed. RCRA U-Series: None listed. Empty sanitary waste. Do not reuse contain service to dispose of this material. Di solvent and burn in a chemical incine	ermine whe elines for th aste genera ire complete container n er. Contact ssolve or n	ether a discar ne classification ators must co e and accura nay be recycl a licensed po nix the materi	on determina nsult state an te classificatio ed or dispose rofessional w al with a com	tion are listed ad local on. ed of as solid aste disposal abustible
		14. Transport Info	rmation			

Revision: 02/11/2020 Supersedes Revision: 12/04/2019

LAND TRANS	SPORT (US DOT):				
DOT Proj	per Shipping Name:	Environmentally hazardou (applies to single container smaller containers are no NOT REGULATED FOR	ers of more than t regulated)	119 gallons -	
DOT Haza UN/NA N	ard Class: umber:				
LAND TRAN	SPORT (Canadian T	DG):			
TDG Shipping Name:		Environmentally hazardous substance, liquid, n.o.s (applies to single containers of more than 119 gallons - smaller containers are not regulated)			
AIR TRANSP	PORT (ICAO/IATA):				
ICAO/IAT	A Shipping Name:	Non-Hazardous for Air Tr	ansport: Non-ha	zardous for air tra	insport.
		15. Regulatory	y Informatio	on	
EPA SARA (S	uperfund Amendment	s and Reauthorization Act o	f 1986) Lists		
<b>CAS #</b> 64742-47-8	Hazardous Compon Hydrotreated light dis	ents (Chemical Name) tillate (petroleum)	<b>S. 302 (EHS)</b> No	<b>S. 304 RQ</b> No	<b>S. 313 (TRI)</b> No
111-76-2	Ethanol, 2-Butoxy- {E Glycol Ether EB}	Ethylene glycol n-butyl ether,	No	No	Yes-Cat. N230
9016-45-9	Poly(oxy-1,2-ethaned .alpha(nonylphenyl) Ethoxylate}	liyl), omegahydr {Nonylphenol	No	No	No
CAS #	Hazardous Compon	ents (Chemical Name)	Other US EPA o	or State Lists	
64742-47-8	Hydrotreated light dis	tillate (petroleum)	•	No; CWA NPDES: ROP.65: No; CA T	
111-76-2	Ethanol, 2-Butoxy- {E Glycol Ether EB}	Ethylene glycol n-butyl ether,		No; CWA NPDES: ROP.65: No; CA T	: No; TSCA: Yes - AC, Title 8: TAC: Cat. IIa,
9016-45-9	Poly(oxy-1,2-ethaned .alpha(nonylphenyl) Ethoxylate}	liyl), omegahydr {Nonylphenol		No; CWA NPDES: AIR, 12(b); CA PRC	: No; TSCA: Yes - DP.65: No; CA TAC, Title 8:

## **16. Other Information**

Revision Date:

02/11/2020

Hazard Rating System:

HEALTH	1	
FLAMMABILIT	Y 2	2
REACTIVITY		
PPE		I

Additional Information About No data available.

HMIS:

This Product:

Company Policy or Disclaimer: THE INFORMATION CONTAINED HEREIN is based upon available information at the time of preparation and is believed to be accurate but is not warranted to be so. Users are advised to confirm in advance of need that the information is current, applicable and suited to the circumstances of use. Vendor assumes no responsibility for injury to vendee or any other user proximately caused by the material if misused or if reasonable safety procedures are not adheared to as stipulated in the data sheet and on the product

Revision: 02/11/2020 Supersedes Revision: 12/04/2019

label. Furthermore, vendor assumes no responsibility for injury or damage caused by abnormal use of this material even if reasonable safety measures are followed.