

# SAFETY DATA SHEET

## POWER PLUS MASTIC REMOVER

Page: 1 of 8

Revision: 03/10/2017  
Supersedes Revision: 05/08/2015

### 1. Product and Company Identification

**Product Code:** 00095R03102017  
**Product Name:** POWER PLUS MASTIC REMOVER  
**Company Name:** TWIN-CHEMICALS, INC  
6175 Hickory Flat Highway  
Suite 100-244  
Canton, GA 30115  
**Phone Number:** (800)442-4958

**Web site address:** www.twinchemicals.com  
**Email address:** sales@twinchemicals.com

**Emergency Contact:** CHEMTREC (emergency only) (800)424-9300  
**Information:** Sales & Information (800)442-4958

### 2. Hazards Identification

Aspiration Toxicity, Category 1  
Acute Toxicity: Oral, Category 4  
Acute Toxicity: Skin, Category 4  
Skin Corrosion/Irritation, Category 2  
Serious Eye Damage/Eye Irritation, Category 2A  
Acute Toxicity: Inhalation, Category 4  
Serious Eye Damage/Eye Irritation, Category 2B  
Aquatic Toxicity (Acute), Category 2  
Aquatic Toxicity (Chronic), Category 2  
Flammable Liquids, Category 4  
Carcinogenicity, Category 2



**GHS Signal Word:** Danger

**GHS Hazard Phrases:** H227 - Combustible liquid.  
H302+312+332 - Harmful if swallowed, in contact with skin or if inhaled.  
H304 - May be fatal if swallowed and enters airways.  
H315+320 - Causes skin and eye irritation.  
H319 - Causes serious eye irritation.  
H351 - Suspected of causing cancer .  
H411 - Toxic to aquatic life with long lasting effects.

**GHS Precaution Phrases:** P201 - Obtain special instructions before use.  
P202 - Do not handle until all safety precautions have been read and understood.  
P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.  
P264 - Wash hands thoroughly after handling.  
P270 - Do not eat, drink or smoke when using this product.  
P271 - Use only outdoors or in a well-ventilated area.  
P273 - Avoid release to the environment.  
P280 - Wear protective gloves/eye protection.

**GHS Response Phrases:** P301+310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.  
P312 - Call a POISON CENTER or doctor/physician if you feel unwell.  
P302+352 - IF ON SKIN: Wash with plenty of soap and water.  
P304+340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

# SAFETY DATA SHEET

## POWER PLUS MASTIC REMOVER

Revision: 03/10/2017

Supersedes Revision: 05/08/2015

contact lenses, if present and easy to do. Continue rinsing. Call a poison control center or physician for treatment advice. Have product container or label with you when calling poison control center or physician.

P308+313 - IF exposed or concerned: Get medical attention/advice.

P330 - Rinse mouth.

P331 - Do NOT induce vomiting.

P332+313 - If skin irritation occurs, get medical advice/attention.

P337+313 - If eye irritation persists, get medical advice/attention.

P362 - Take off contaminated clothing and wash before re-use.

P363 - Wash contaminated clothing before reuse.

P391 - Collect spillage.

P370+378 - In case of fire, use water spray, dry chemical, carbon dioxide or appropriate foam to extinguish.

### GHS Storage and Disposal Phrases:

P403+235 - Store in cool/well-ventilated place.

P405 - Store locked up.

P501 - Dispose of contents/container to qualified waste facility according to regulations.

### Potential Health Effects (Acute and Chronic):

Prolonged or repeated skin contact may cause defatting and dermatitis.

Chronic: May cause liver and kidney damage. Sophisticated modeling has clearly proven that 2-butoxyethanol does not build up in the body under any kinds of normal use.

### Inhalation:

Harmful if inhaled. May cause narcotic effects in high concentration. May cause lung damage. May cause central nervous system effects such as nausea and headache. Material is irritating to mucous membranes and upper respiratory tract. Aspiration may lead to pulmonary edema. Vapors may cause dizziness or suffocation.

### Skin Contact:

May cause irritation with burning pain, itching and redness. Substance is rapidly absorbed through the skin. Causes symptoms similar to those of inhalation. Skin sensitization testing with human volunteers produced negative results. A skin notation is not recommended by ACGIH, based on estimates from physiologically based pharmacokinetic models which indicate that, even in worst-case dermal-exposure scenarios, 2-butoxyethanol is not absorbed in amounts sufficient to cause red blood cell hemolysis in humans. May cause skin irritation.

Prolonged and/or repeated contact may cause irritation and/or dermatitis.

### Eye Contact:

Causes redness and pain. Causes mild eye irritation.

### Ingestion:

Aspiration hazard. May cause irritation of the digestive tract. Harmful if swallowed. May cause gastrointestinal irritation with nausea, vomiting and diarrhea. Prolonged or repeated exposure may cause allergic reactions in certain sensitive individuals. Aspiration of material into the lungs may cause chemical pneumonitis, which may be fatal.

## 3. Composition/Information on Ingredients

CAS #	Hazardous Components (Chemical Name)	Concentration
64742-47-8	Hydrotreated light distillate (petroleum)	15.0 -30.0 %
111-76-2	Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, Glycol Ether EB}	4.0 -10.0 %
9016-45-9	Poly(oxy-1,2-ethanediyl), .alpha.-(nonylphenyl)-.omega.-hydr {Nonylphenol Ethoxylate}	2.0 -5.0 %
64742-94-5	Solvent naphtha (petroleum), Heavy arom.	60.0 -80.0 %

# SAFETY DATA SHEET

## POWER PLUS MASTIC REMOVER

Page: 3 of 8

Revision: 03/10/2017

Supersedes Revision: 05/08/2015

### 4. First Aid Measures

#### Emergency and First Aid Procedures:

<b>In Case of Inhalation:</b>	If inhaled, remove to fresh air. If breathing is difficult, give oxygen. Get medical aid immediately. Remove from exposure and move to fresh air immediately. Do NOT use mouth-to-mouth resuscitation.
<b>In Case of Skin Contact:</b>	In case of contact, flush skin with plenty of water. Remove contaminated clothing and shoes. Get medical aid if irritation develops and persists. Wash clothing before reuse. Get medical aid if irritation develops or persists.
<b>In Case of Eye Contact:</b>	Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid immediately. If irritation develops, get medical aid.
<b>In Case of Ingestion:</b>	Potential for aspiration if swallowed. Get medical aid immediately. Never give anything by mouth to an unconscious person. If vomiting occurs naturally, have victim lean forward. Call a poison control center. If swallowed, wash out mouth with water provided person is conscious. Call a physician. If conscious and alert, rinse mouth and drink 2-4 cupfuls of milk or water.
<b>Signs and Symptoms Of Exposure:</b>	Exposure can cause: Nausea, headache, and vomiting. To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.
<b>Note to Physician:</b>	None known.

### 5. Fire Fighting Measures

<b>Flash Pt:</b>	> 62.00 C Method Used: Estimate
<b>Explosive Limits:</b>	LEL: No data. UEL: No data.
<b>Autoignition Pt:</b>	No data.
<b>Suitable Extinguishing Media:</b>	Use water spray, dry chemical, carbon dioxide, or appropriate foam. Suitable: In case of fire, use water, dry chemical, chemical foam, or alcohol-resistant foam.
<b>Fire Fighting Instructions:</b>	As in any fire, wear a self-contained breathing apparatus in pressure-demand, MSHA/NIOSH (approved or equivalent), and full protective gear. During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion. Use water spray to keep fire-exposed containers cool. Will burn if involved in a fire. Combustible liquid and vapor. Protective Equipment: Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes. Vapors may be heavier than air. They can spread along the ground and collect in low or confined areas. Containers may explode when heated.
<b>Flammable Properties and Hazards:</b>	No data available.
<b>Hazardous Combustion Products:</b>	No data available.

# SAFETY DATA SHEET

## POWER PLUS MASTIC REMOVER

Page: 4 of 8

Revision: 03/10/2017  
Supersedes Revision: 05/08/2015

### 6. Accidental Release Measures

#### Steps To Be Taken In Case Material Is Released Or Spilled:

Use proper personal protective equipment as indicated in Section 8.

Spills/Leaks: Absorb spill with inert material (e.g. vermiculite, sand or earth), then place in suitable container. Avoid runoff into storm sewers and ditches which lead to waterways. Clean up spills immediately, observing precautions in the Protective Equipment section. Remove all sources of ignition. Provide ventilation. Wear a self contained breathing apparatus and appropriate personal protection. (See Exposure Controls, Personal Protection section). Use a spark-proof tool. Do not let this chemical enter the environment. PROCEDURE(S) OF PERSONAL PRECAUTION(S)

Wear respirator, chemical safety goggles, rubber boots, and heavy rubber gloves. Methods for cleaning up.

Absorb on sand or vermiculite and place in closed containers for disposal. Ventilate area and wash spill site after material pickup is complete. Clean up residual material by washing area with a 2-5% solution of soda ash.

### 7. Handling and Storage

#### Precautions To Be Taken in Handling:

Wash thoroughly after handling. Avoid contact with eyes, skin, and clothing. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep container tightly closed. Avoid ingestion and inhalation. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose empty containers to heat, sparks or open flames. Use spark-proof tools and explosion proof equipment. Keep away from heat, sparks and flame. Do not ingest or inhale. Use only in a chemical fume hood. User Exposure: Do not breathe vapor. Use only in a well-ventilated area.

#### Precautions To Be Taken in Storing:

Keep away from sources of ignition. Store in a tightly closed container. Store in a cool, dry, well-ventilated area away from incompatible substances. Store in a cool, dry place. Suitable: Keep away from heat, sparks and flame.

### 8. Exposure Controls/Personal Protection

CAS #	Partial Chemical Name	OSHA TWA	ACGIH TWA	Other Limits
64742-47-8	Hydrotreated light distillate (petroleum)	No data.	TLV: 200 mg/m <sup>3</sup>	No data.
111-76-2	Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, Glycol Ether EB}	PEL: 50 ppm	TLV: 20 ppm	No data.
9016-45-9	Poly(oxy-1,2-ethanediyl), .alpha.-(nonylphenyl)-.omega.-hydr {Nonylphenol Ethoxylate}	No data.	No data.	No data.
64742-94-5	Solvent naphtha (petroleum), Heavy arom.	No data.	No data.	No data.

#### Personal Protective Equipment Symbols:



#### Respiratory Equipment (Specify Type):

Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU). Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi- purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. Hand: Compatible chemical-resistant gloves.

#### Eye Protection:

Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166. Chemical safety goggles.

#### Protective Gloves:

Wear appropriate protective gloves to prevent skin exposure.

#### Other Protective Clothing:

Wear appropriate protective clothing to prevent skin exposure.

# SAFETY DATA SHEET

## POWER PLUS MASTIC REMOVER

Page: 5 of 8

Revision: 03/10/2017

Supersedes Revision: 05/08/2015

<b>Engineering Controls (Ventilation etc.):</b>	Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Use adequate ventilation to keep airborne concentrations low. Use explosion-proof ventilation equipment. Use only under a chemical fume hood. Safety shower and eye bath.
<b>Work/Hygienic/Maintenance Practices:</b>	Wash thoroughly after handling.

### 9. Physical and Chemical Properties

<b>Physical States:</b>	[ ] Gas [ X ] Liquid [ ] Solid
<b>Appearance and Odor:</b>	Clear liquid. solvent odor.
<b>pH:</b>	NP
<b>Melting Point:</b>	NA -70.00 - 58.00 C
<b>Boiling Point:</b>	171.00 C - 401.00 C
<b>Flash Pt:</b>	> 62.00 C Method Used: Estimate
<b>Evaporation Rate:</b>	< 1 (H <sub>2</sub> O=1)
<b>Flammability (solid, gas):</b>	No data available.
<b>Explosive Limits:</b>	LEL: No data. UEL: No data.
<b>Vapor Pressure (vs. Air or mm Hg):</b>	0.59 MM_HG at 20.0 C
<b>Vapor Density (vs. Air = 1):</b>	4.7
<b>Specific Gravity (Water = 1):</b>	0.89 - 0.90 at 20.0 C
<b>Solubility in Water:</b>	Emulsifiable
<b>Octanol/Water Partition Coefficient:</b>	No data.
<b>Autoignition Pt:</b>	No data.
<b>Decomposition Temperature:</b>	No data.
<b>Viscosity:</b>	Water thin

### 10. Stability and Reactivity

<b>Stability:</b>	Unstable [ ] Stable [ X ]
<b>Conditions To Avoid - Instability:</b>	ignition sources, Incompatible materials.
<b>Incompatibility - Materials To Avoid:</b>	Strong acids. Strong bases, Aluminum, Oxidizing agents.
<b>Hazardous Decomposition or Byproducts:</b>	Nitrogen oxides, Carbon monoxide, oxides of sulfur, irritating and toxic fumes and gases.
<b>Possibility of Hazardous Reactions:</b>	Will occur [ ] Will not occur [ X ]
<b>Conditions To Avoid - Hazardous Reactions:</b>	No data available.

## 11. Toxicological Information

**Toxicological Information:** Epidemiology: No information found.  
Teratogenicity: No information available. Reproductive Effects: Mutagenicity:  
Neurotoxicity: Epidemiological studies involving petroleum refinery workers indicate persons with routine exposure to petroleum or one of its constituents may be at an increased risk to the development of benign neoplasms, digestive tract cancer, and skin cancer.

**Carcinogenicity/Other Information:** CAS# 64742-47-8: Not listed by ACGIH, IARC, NTP, or CA Prop 65. CAS# 111-76-2: ACGIH: A3 - Confirmed animal carcinogen with unknown relevance to humans. California: Not listed. NTP: Not listed. IARC: Not listed. CAS# 64742-94-5: Not listed by ACGIH, IARC, NTP, or CA Prop 65.

CAS #	Hazardous Components (Chemical Name)	NTP	IARC	ACGIH	OSHA
64742-47-8	Hydrotreated light distillate (petroleum)	n.a.	n.a.	A4	n.a.
111-76-2	Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, Glycol Ether EB}	n.a.	3	A3	n.a.
9016-45-9	Poly(oxy-1,2-ethanediyl), .alpha.-(nonylphenyl)-.omega.-hydr {Nonylphenol Ethoxylate}	n.a.	n.a.	n.a.	n.a.
64742-94-5	Solvent naphtha (petroleum), Heavy arom.	n.a.	n.a.	n.a.	n.a.

## 12. Ecological Information

**General Ecological Information:** Environmental: TERRESTRIAL FATE: Based on a recommended classification scheme, an estimated Koc value of 67,, determined from an experimental log Kow and a recommended regression-derived equation, indicates that ethylene glycol mono-n-butyl ether is expected to have high mobility in soil. An estimated BCF value of 2.5 was calculated for ethylene glycol mono-n-butyl ether, using an experimental log Kow of 0.83 and a recommended regression-derived equation. According to a recommended classification scheme, this BCF value suggests that bioconcentration in aquatic organisms is low.  
Physical: No information found.  
Other: An estimated BCF value of 2.5,, from an experimental log Kow, suggests that ethylene glycol mono-n-butyl ether bioconcentration in aquatic organisms will be low, according to a recommended classification scheme. ELIMINATION.

## 13. Disposal Considerations

**Waste Disposal Method:** Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. US EPA guidelines for the classification determination are listed in 40 CFR Parts 261. Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification.  
RCRA P-Series: None listed.  
RCRA U-Series: None listed. Empty container may be recycled or disposed of as solid sanitary waste. Do not reuse container. Contact a licensed professional waste disposal service to dispose of this material. Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber.

## 14. Transport Information

# SAFETY DATA SHEET

## POWER PLUS MASTIC REMOVER

Revision: 03/10/2017  
Supersedes Revision: 05/08/2015

### LAND TRANSPORT (US DOT):

**DOT Proper Shipping Name:** Environmentally hazardous substance, liquid, n.o.s  
(applies to single containers of more than 119 gallons -  
smaller containers are not regulated)  
NOT REGULATED FOR DOMESTIC TRANSPORT.

**DOT Hazard Class:**

**UN/NA Number:**

### LAND TRANSPORT (Canadian TDG):

**TDG Shipping Name:** Environmentally hazardous substance, liquid, n.o.s  
(applies to single containers of more than 119 gallons -  
smaller containers are not regulated)  
Not regulated under U.S. Department of Transportation regulations (29 CFR)

### AIR TRANSPORT (ICAO/IATA):

**ICAO/IATA Shipping Name:** Non-Hazardous for Air Transport: Non-hazardous for air transport.

## 15. Regulatory Information

### EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS #	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
64742-47-8	Hydrotreated light distillate (petroleum)	No	No	No
111-76-2	Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, Glycol Ether EB}	No	No	Yes-Cat. N230
9016-45-9	Poly(oxy-1,2-ethanediyl), .alpha.-(nonylphenyl)-.omega.-hydr {Nonylphenol Ethoxylate}	No	No	No
64742-94-5	Solvent naphtha (petroleum), Heavy arom.	No	No	No

CAS #	Hazardous Components (Chemical Name)	Other US EPA or State Lists
64742-47-8	Hydrotreated light distillate (petroleum)	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No
111-76-2	Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, Glycol Ether EB}	CAA HAP,ODC: Yes - Cat.; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No
9016-45-9	Poly(oxy-1,2-ethanediyl), .alpha.-(nonylphenyl)-.omega.-hydr {Nonylphenol Ethoxylate}	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory, 8A PAIR, 12(b); CA PROP.65: No
64742-94-5	Solvent naphtha (petroleum), Heavy arom.	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No

## 16. Other Information

**Revision Date:** 03/10/2017

**Hazard Rating System:**

HEALTH	1
FLAMMABILITY	2
PHYSICAL	0
PPE	B

**HMIS:**

**Additional Information About** No data available.

**This Product:**

**Company Policy or**

**Disclaimer:**

THE INFORMATION CONTAINED HEREIN is based upon available information at the time of preparation and is believed to be accurate but is not warranted to be so. Users are advised to confirm in advance of need that the information is current, applicable and



# **SAFETY DATA SHEET**

## **POWER PLUS MASTIC REMOVER**

Revision: 03/10/2017

Supersedes Revision: 05/08/2015

suited to the circumstances of use. Vendor assumes no responsibility for injury to vendee or any other user proximately caused by the material if misused or if reasonable safety procedures are not adhered to as stipulated in the data sheet and on the product label. Furthermore, vendor assumes no responsibility for injury or damage caused by abnormal use of this material even if reasonable safety measures are followed.